



RADE KONCAR CONTACTOR CNN22
22A/11kW (AC3, 400V/50Hz); 30A(AC1)
 In conformity with standard IEC 60947-4-1

Contactor type		CNN 22	
Mechanical endurance	make/brake operations	x10 ⁶	5
Insulation rating		V	690
Permissible ambient temperature		°C	from -25 to +55
Consumption of electromagnet in cold state with Un			
AC operated	closing	VA	62
	P.F. closed	VA	0.75
DC operated	closing	W	7
	P.F. closed	W	0.3
			123
			2.8
Coil voltage tolerances			0.85-1.1Un
duration of making and breaking			
(values are also valid for voltages of electromagnet from 0.8 to 1.1 Un for each in cold and warm state).			
Total breaking time is addition of opening time and duration of electric arc.			
AC operated	closing time	ms	12 to 22
	opening time	ms	4 to 19
	duration of electric arc	ms	10
Frequency of switching operations			
without thermal relay			
utilization category	AC1	s/h	1000
	AC2, AC3	s/h	750
	AC4	s/h	250
with thermal relay			
		s/h	15
			8.2/5
			and
			4.9/10
Short-circuit protection of			
contactors without overload relays			
Main circuit			
With fuse links			
acc. To IEC 60947-4-1	Type of coord. "1" gl/gG	A	50
DIN VDE 0660 Part 102	Type of coord. "2"	A	35
Sizes of connection conductors			
for contact without thermal relay			
main circuit	single-wire conductors	mm ²	2.5-10
	multi-wire conductor with cable shoe	mm ²	2.5-10
	Screw		M4
	Screw head		PZ2
auxiliary circuit	Tightening torque	Nm	1.4
	single-wire conductor	mm ²	1-2.5
	multi-wire conductor with cable shoe	mm ²	0.75-1.5
	Screw		M3.5
	Screw head		PZ2
	Tightening torque	Nm	0.8
Loadability of auxiliary contacts			
Rated continuous current I _{th} ; 40 °C		A	-
rated operational current I _e /AC15	for 24V	A	-
	230V	A	-
	400V	A	-
	500V	A	-
	690V	A	-
	rated operational current I _e /DC13	for 24V	A
	110V	A	-

	230V	A	-
Load carrying capacity of the main contacts			
rated continuous current I _{th}		A	40
AC1 utilization category		A	40
rated operational current I _e /AC1		A	40
AC2 and AC3 utilization categories			
	for 230V	kW	5.5
(slip-ring and cage motors at 50Hz)	400V	kW	11
	690V	kW	11
AC4 utilization category			
(electrical endurance of contacts:120.000)			
rated current	I _e /AC4	A	7
ratings of squirrel-cage motors at 50Hz	for 230V	kW	1.7
	400V	kW	3.3
	500V	kW	3.3
	690V	kW	3.3
Loadability by direct current			
DC1 utilization category, non-inductive loads L/R1 ms			
rated operational current I _e	for 24V	A	20
through one pole	48V	A	20
	110V	A	2.1
	220V	A	0.8
	440V	A	0.6
	600V	A	0.6
through three poles connected in series	for 24V	A	20
	48V	A	20
	110V	A	20
	220V	A	20
	440V	A	1.3
	600V	A	1
utilization category DC3 to DC5			
series and shunt motors (L/R15 ms)			
rated operational current I _e	for 24V	A	20
through one pole	48V	A	5
	110V	A	1.5
	220V	A	0.75
	440V	A	0.09
	600V	A	0.06
through three poles connected in series	for 24V	A	20
	48V	A	20
	110V	A	20
	220V	A	6
	440V	A	0.2
	600V	A	0.2

