



RADE KONCAR CONTACTOR **CKN25**
25A/11kW (AC3, 400V/50Hz); 40A(AC1)

Contactor type			CKN 25	
Mechanical endurance	make/brake operations		x10 ⁶	5
Insulation rating			V	690
Permissible ambient temperature			°C	from -25 to +55
Consumption of electromagnet in cold state with Un				
AC operated	closing		VA	62
	P.F.			0,75
	closed		VA	7
	P.F.			0,3
DC operated	closing		W	123
	closed		W	2,8
Coil voltage tolerances			0.85-1.1Un	
duration of making and braking				
(values are also valid for voltages of electromagnet from 0.8 to 1.1 Un for each in cold and warm state).				
Total breaking time is addition of opening time and duration of electric arc.				
AC operated	closing time		ms	12 to 22
	opening time		ms	4 to 19
	duration of electric arc		ms	10
Frequency of switching operations				
without thermal relay				
	utilization category	AC1	s/h	1000
		AC2, AC3	s/h	750
		AC4	s/h	250
with thermal relay				
			s/h	15
Resistivity to shocks	(square shock)		g/ms	8.2/5 and 4.9/10
Short-circuit protection of contactors without overload relays				
Main circuit				
With fuse links				
acc. To IEC 60947-4-1	Type of coord. "1" gI/gG		A	50
DIN VDE 0660 Part 102	Type of coord. "2"		A	35
Sizes of connection conductors				
for contact without thermal relay				
main circuit	single-wire conductors		mm ²	2.5-10
	multi-wire conductor with cable shoe		mm ²	2.5-10
	Screw			M4
	Screw head			PZ2
	Tightening torque		Nm	1,4
auxiliary circuit	single-wire conductor		mm ²	1-2.5
	multi-wire conductor with cable shoe		mm ²	0.75-1.5
	Screw			M3.5
	Screw head			PZ2
	Tightening torque		Nm	0,8
Loadability of auxiliary contacts				
Rated continuous current Ith ; 35C			A	-
rated operational current Ie/AC15	for 24V		A	-
	230V		A	-
	400V		A	-
	500V		A	-
	690V		A	-
			A	-
rated operational current Ie/DC13	for 24V		A	-
	110V		A	-
	230V		A	-

Load carrying capacity of the main contacts

rated continuous current I_{th}

AC1 utilization category

A 40

rated operational current $I_e/AC1$

A 40

AC2 and AC3 utilization categories

for 230V

kW 5,5

(slip-ring and cage motors at 50Hz)

400V

kW 11

690V

kW 15

AC4 utilization category

(electrical endurance of contacts:120.000)

rated current

$I_e/AC4$

A 8,5

ratings of squirrel-cage motors at 50Hz

for 230V

kW 2,2

400V

kW 4

500V

kW 4

690V

kW 4

Loadability by direct current

DC1 utilization category, non-inductive loads L/R1 ms

rated operational current I_e

for 24V

A 35

through one pole

48V

A 20

110V

A 4,5

220V

A 1

440V

A 0,6

600V

A 0,6

through three poles connected in series

for 24V

A 35

48V

A 35

110V

A 35

220V

A 35

440V

A 2,9

600V

A 1,4

utilization category DC3 to DC5

series and shunt motors (L/R15 ms)

rated operational current I_e

for 24V

A 20

through one pole

48V

A 5

110V

A 2,5

220V

A 1

440V

A 0,09

600V

A 0,06

through three poles connected in series

for 24V

A 35

48V

A 35

110V

A 35

220V

A 10

440V

A 0,6

600V

A 0,3

