



RADE KONCAR CAPACITOR CONTACTOR CNNK 5

In conformity with standard IEC 60947-4-1

Contactor type			CNNK 5
Capacitor rating			
at operating voltage	230V	kVAr	2,8
	400-440V	kVAr	5
50/60 Hz	500-550V	kVAr	5,5
	660-690V	kVAr	7,5
Rated operational current Ie/AC at 400 V		A	7,2
Insulation rating	U	V	690
Permissible ambient temperature		°C	-25 to +55
Rated impuls withstand voltage	Uimp	kV	6
consumption of electromagnet in cold state with Un Ac operated			
	closing	VA	62
	p.f. closed	VA	0,75
	p.f.		7
			0,3
Coil	Voltage tolerances		0.85-1.1 Un
	Tightening torque	Nm	0,8
	Terminal screw/screw head		M3.5/PZ2
Degree of protection			IP20
Maximum permissible fuse ratings			
main circuit	gL/gG	A	25
auxiliary circuit		A	16
Frequency of switching operations		s/h	240
Electrical endurance		min.	120.000
Sizes of connecting conductors			
-main circuit			
multi-wire conductor		mm ²	1.5-6
multi-wire conductor with cable shoe		mm ²	1.5-6
Terminal screw			M4
Screw head			PZ2
Tightening torque		Nm	1,2
auxilliary circuit			
multi-wire conductor		mm ²	1-2.5
multi-wire conductor			

with cable shoe	mm ²	0.75-1.5
Terminal screw		M3.5
Screw head		PZ2
Tightening torque	Nm	0.8
Loadability of auxiliary contacts rated continuous current I _{th} : 35	A	10
AC rated operational current I _e /AC 15		
for 230V	A	6
400V	A	4
500V	A	2
690V	A	1

CNNK 5

Drilling plan (mm)

