



RADE KONČAR CAPACITOR CONTACTOR CNNK 65

In conformity with standard IEC 60947-4-1

Contactor type			CNNK 65
Capacitor rating			
at operating voltage	230V	kVAr	32
	400-440V	kVAr	66
50/60 Hz	500-550V	kVAr	75
	660-690V	kVAr	85
Rated operational current Ie/AC-6b at 400 V		A	94
Rated operational current Ith at 40 °C		A	130
Insulation rating	Ui	V	1000
Permissible ambient temperature		°C	-25 to +55
Rated impuls withstand voltage Uimp		kV	8
consumption of electromagnet in cold state with Un Ac operated			
	closing	VA	204
	p.f.		0.54
	closed	VA	16
	p.f.		0.26
Coil	Voltage tolerances		0.85-1.1 Un
	Tightening torque	Nm	0.8
	Termal screw/screw head		M3.5/PZ2
Degree of protection			IP20
Maximum permissible fuse ratings			
main circuit gL/gG		A	160
auxiliary circuit		A	16
Frequency of switching operations		s/h	100
Electrical endurance		min.	100,000
Sizes of connecting conductors			
-main circuit			
multi-wire conductor		mm ²	25-50
multi-wire conductor with cable shoe		mm ²	
Termal screw			M8
Screw head			⬡ 4
Tightening torque		Nm	4-4.5
auxilliary circuit			

multi-wire conductor	mm ²	1-2.5
multi-wire conductor with cable shoe	mm ²	0.75-1.5
Terminal screw		M3.5
Screw head		PZ2
Tightening torque	Nm	0.8
Loadability of auxiliary contacts rated continuous current I _{th} : 35	A	16
AC rated operational current I _e /AC 15		
for 230V	A	10
400V	A	6
500V	A	4
690V	A	2

CNNK 65

Drilling plan (mm)

